

Escape Sign Luminaire Profile 5001 K CG-S









- Safety luminaire with rounded enclosure outline and clear cover made of plastic.
- With 30 % luminous flux during mains operation and 100 % luminous flux during battery operation – especially suitable for darkened rooms
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditure with STAR technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit



5001 K CG-S

| Viewing distance | | 17 m |
|--|-----------|--|
| Housing material | Cover | Plastic |
| | Enclosure | Aluminium |
| Weight incl. cover | | 1.4 kg |
| Housing colour | | White / Silver |
| Type of mounting | | Wall mounting |
| Connection terminals | | Loop terminals 3 x 2.5 mm ² |
| Connection voltage | | 220 – 240 V AC, 50/60 Hz 176 – 275 V DC |
| Current consumption with battery operation | | 60 mA |
| Power consumption mains operation | | 14 VA |
| Permissible ambient temperature | | -10 °C to +40 °C |
| Light source | | Incandescent lamp 2 x 7 W |

Ordering details

| Type | Scope of supply | Order No. |
|---------------------------|--|----------------|
| 5001 K CG-S | Luminaire with CEWA GUARD monitoring and address switch, without cover | 4 0071 341 897 |
| Cover PL acc. to DIN 4844 | Cover with pictogram  | 4 0071 349 621 |
| Cover PR acc. to DIN 4844 | Cover with pictogram  | 4 0071 349 622 |
| Cover PU acc. to DIN 4844 | Cover with pictogram  | 4 0071 349 623 |
| Cover PL | Cover with pictogram  | 4 0071 345 448 |
| Cover PR | Cover with pictogram  | 4 0071 345 449 |
| Cover PU | Cover with pictogram  | 4 0071 345 450 |

Accessories

| Type | Scope of supply | Order No. |
|----------------------|---|----------------|
| Surface wall bracket | Quick-mounting set for surface mounting | 4 0071 337 878 |
| Wire guard | | 400 71 348 370 |

With 30 % luminous flux during mains operation and 100 % luminous flux ratio during battery operation, especially suitable for cinema, theatre etc.

Dimensions in mm

