


# Central Monitoring System CG-Controller CGLine 400



CG Controller CGLine 400



removable configuration and log book memory SD



PC with CEAG software for programming and evaluation of the SD

- Control and monitoring of up to 400 CGLine self contained luminaires
- Automatic luminaire search function
- Automatic function test and duration test
- Test results in plain text with details of luminaire ID, abbreviated address, individual luminaire name and type of fault
- Log book: storage of test results for a period of 4 years
- Status display per luminaire
- Potential-free contact freely programmable for: battery operation, function test, duration test, communication fault, luminaire fault, charging fault
- Password protection
- Free assignment of short address and individual names (20 characters per luminaire)
- Memory card for saving of configuration and inspection book
- Configuration and log book evaluation on PC via SD card and corresponding CEAG software for PC

Dimensions in mm (H x W x D)	184 x 240 x 112
Housing	Plastic RAL 7035, with transparent cover
Protection rate of housing (IEC 529)	IP 65
Supply voltage	230 V 50 Hz / 24 V DC
Insulation class	II
Ambient temperature	-5 °C to + 40 °C
Connection terminals/plug-in terminals	2.5 mm <sup>2</sup>
Display	Illuminated display, alphanumeric, 4 x 20 characters
Keyboard	Foil keyboard 4 x 4
Potential-free contact	1 x UM, 24 V 0.5 A; freely programmable
LED display for	Operation / test / fault

## Order information

Type	Scope of delivery	Order No.
CG-Controller CGLine 400	Controller in housing incl. CG-S BUS interface and SD	4 0071 347 901
SD memory card (replacement card)	SD card formatted for CG-Controller CGLine 400	4 0071 347 872
SD card reader	SD card reader for USB port	4 0064 070 561
Software	PC software for CGLine 400, for alternative configuration and log book evaluation via PC	4 0071 347 535
I/O interface plug-in card	for connection to the F3 module	4 0071 347 985

