


Central Visualisation CGLine WEB-Interface




CGLine Web-Interface
with integrated webservice

- E-mail client for up to 10 e-mail recipients with confirmation function and parameterisable messages
- Up to 8 CGLine WEB interfaces with up to 3,200 luminaires to CGVision for complete visualisation
- Automatic luminaire search function (no manual addressing required)
- Automatic function test, test period can be freely defined
- Automatic duration test, test period can be freely defined
- Blocking of emergency light function (completely or per bus line)
- Luminaires with maintained mode can be switched in non-maintained mode (completely or per bus line)
- Free input of luminaire target location designations each with 20 characters, 100 characters. Supplementary information, and short address assignment via CGVision or convenient PC software
- Password protection
- Removable configuration and inspection book memory via SD memory card for a period of at least 4 years
- Evaluation of the log book on SD memory card via optional card reader and CEAG software on conventional PC



| | |
|---------------------------------|--------------------------|
| Dimensions | 175 x 126 x 60 mm |
| Housing type | For DIN rail 10 TE |
| Voltage supply (typ.) | 230 V AC |
| Power consumption | < 4 Watt |
| Connection terminals | max. 2.5 mm ² |
| Permissible ambient temperature | 0 °C ... 35 °C |
| Storage temperature | -20°C ... 70°C |
| Protection rating | IP 20 |



Order information

| Type | Scope of delivery | Order No. |
|--------------------------------------|---|----------------|
| CGLine Web-Interface | module in surface mounted housing for DIN rail | 4 0071 360 020 |
| SD memory card (replacement card) | SD card formatted for CG-Controller CGLine 400 | 4 0071 347 872 |
| SD card reader | SD card reader USB-Port | 4 0064 070 561 |
| Software | PC software for CGLine 400, for alternative configuration and log book evaluation via PC | 4 0071 347 535 |



6